

ECOFOAM ADVANCED

ULTRA-HIGH PERFORMANCE ALKALINE LONG CLING FOAM CLEANER

- For fat and protein removal on heavily soiled areas
- Long cling foam
- Remains fully effective regardless of water hardness



RECOMMENDED USAGE



Application

Use to spray the roof, walls and posts with a pressure washer set at a low pressure with a wide angled jet or via foam generating equipment.

Remove all gross soiling. Foam all surfaces with Ecofoam Advanced. Wash down thoroughly with clean water.



Dilution Rates

Apply via a foaming lance at a dilution rate of 1:100 for normal conditions or 1:50 for heavy soiling. Leave for 10 - 30 minutes dependent on the level of soiling then rinse off thoroughly with clean water.



Composition

A formulation of chelating agents, surfactants and alkaline builders.



Storage: Store in a dry place away from acids

Pack Size: 4x5, 25, 200 & 1000 litre

Shelf Life: 2 years from date of manufacture



FOR HEALTH & SAFETY INFORMATION, REFER TO THE SAFETY DATA SHEET

KILCO (INTERNATIONAL) LTD.
BROOMHOUSES 2 INDUSTRIAL ESTATE
OLD GLASGOW ROAD, LOCKERBIE.
DG11 2SD

Tel: +44 (0) 1576 205 480
Fax: +44 (0) 1576 205 483
Email: enquiries@kilco.co.uk